



PACUR™ RPETG Clear Copolyester Sheet [when available]

Pacur™ RPETG Clear Sheet is extruded from a mixture of Pacur's internally-generated Clear PETG recyclable material and regrind (scrap) material obtained from outside sources. Material obtained from the outside sources has wide variations of quality level. This material is meant to be used in "utility" non-FDA applications.

PACUR™ RPETG CLEAR SHEET SPECIFICATIONS (Available in Roll Stock Only)

GAUGE:	.005" - .035" (125mi to 900mi)
WIDTH:	Maximum 52" (1,500mm)
ROLL DIAMETER:	Slit Rolls - 24" (600mm) Jumbo Rolls - 40" (1,000mm)
CORE SIZES:	3" (76mm) or 6" (152mm) I.D.
COLOR/TINTS	Custom Colors Available on Request
COATINGS:	Silicone Coating Available

PACUR™ RPETG CLEAR SHEET PROPERTIES

PROPERTY	UNITS	PACUR™ RPETG CLEAR
Density	gm/cc	1.27
Yield @ .010"	in ² /lb	2,180
Haze @ .010"	%	1.0
Tensile Strength @ Yeild	PSI	5,900
Tensile Modulus of Elasticity	PSI	250,000
Dart Impact @ 73°F	1/2" dart gm @ 26"	325
Dart Impact @ -20°F	1/2" dart gm @ 26"	300
Oxygen Transmission Rate	cc/mil/m ² /24hrs/atm	394
Oxygen Transmission Rate	cc/mil/100 in ² /24hrs/atm	25.4
Water Vapor Transmission Rate	gm/mil/100 in ² /24hrs/atm	3.9
I.V. Range	Centistokes	0.59-0.72

The information contained herein is true and accurate to the best of our knowledge; however; it is presented without any guarantees and without assumption of any liabilities as a result of the use of the information herein.

#5/MKT/REV-05/08

3555 MOSER STREET • OSHKOSH, WISCONSIN 54901 • (920) 236-2888 • FAX (920) 236-2882
www.pacur.com

PACUR is an ISO 9001:2000 company